


DIAMETRIC 24" X 24" BLACK (P) Porcelain



PART NUMBER	PROFILE	AVAILABILITY
PO2348-2424PO	TILE	FACTORY OUTLET
GROUT JOINT	DIMENSIONS	THICKNESS
1/16"	23.64" x 23.64" = 3.875 sqft	3/8"
NOTES		
Available nationwide.		
Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.		

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL
Yes	Residential Floor Use Only	Residential	Yes	Wall Only	Wall Only	Yes
BACKSPLASH	FIREPLACE SURROUND	INTERIOR				
Yes	Yes	Yes				

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	102	Breaking Strength - ISO 10545-4	1919N
Frost Resistance - ISO 10545-9	Pass	Bending Resistance - ISO 10545-4	R ³ 35 N/mm ²
Regularity of Length & Width - ISO 10545-2	600x600mm +/- 0.6mm 298x600mm +/- 0.6mm	Regularity of Rectangularity - ISO 10545-2	Ø+/- 0.4mm
Regularity of Straightness of Sides - ISO 10545-2	Ø+/- 0.5mm	Resistance to Household Chemicals - ISO 10545-13	UA
Resistance to Swimming Pool Salts - ISO 10545-13	UA	Surface Flatness - ISO 10545-2	300mm (0.6+0.7mm) 600mm (0.7+0.9mm)
Water Absorption - ISO 10545-3	0.07%		
DCOF - ANSI A.137.1	< 0.42		