

WIDE 24" X 48" OLIVE (M) Porcelain



PART NUMBER

PROFILE TILE

AVAILABILITY

PO2133-2448M0 GROUT JOINT

DIMENSIONS

THICKNESS

AVAILABLE ON REQUEST

1/16"

 $23.62'' \times 47.24'' = 7.750$ sqft

3/8"

ORIGIN

Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET R AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

Water Absorption - ISO 10545-3	0.2%	TECHNICAL DATA				
Resistance to Swimming Pool Salts - ISO 10545-13	Compliant	Surface Flatness - ISO 10545-2	Compliant			
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	Compliant			
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant			
Bending Resistance - ISO 10545-4	Compliant	Reaction to Fire - EN 13501-1	Alfl			
Frost Resistance - ISO 10545-12	Compliant	Impact Resistance - ISO 10545-5	Compliant			
Coefficient of Thermal Linear Expansion - ISO 10545-8	² 7_MK-1	Coefficient of Friction - B.C.R.A. Rep. CEC/81	Asciutto > 0.40, Bagnato > 0.4			
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant			
FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION			

FEATURES & STANDARD

SPECIFICATION

DCOF - ANSI A. 137. 1

> 0.42 Wet

LEED

EQ112

Low₁Emitting Materials Recycled Content akdo.com

Zero V.O.C. Emissions

20% pre-consumer recycled material

COMMERCIAL · HOSPITALITY · RESIDENTIAL