

AKDO®

ARCHITETTO

*Harmonious. Remarkable. Lively.
Revitalize and Inspire.*

Far Beyond the Surface





Architetto Angolo Ash Gray (H)

MB1809-ANGOHO



Architetto Angolo Calacatta (H)

MB1203-ANGOHO



Architetto Angolo Calacatta (H) w/ Brass

MB1203-ANGOH1



Architetto Angolo Carrara Bella (H)

MB1604-ANGOHO




Architetto Angolo Carrara Bella (H)

w/ Stainless Steel

MB1604-ANGOH1

ARCHITETTO

Compasso



Architetto Compasso Ash Gray (H&SB)
MB1809-COMP00



Architetto Compasso Calacatta (H&SB)
MB1203-COMP00



Architetto Compasso Calacatta (H) w/ Brass
MB1203-COMPH0



Architetto Compasso Carrara Bella (H&SB)
MB1604-COMP00



Architetto Compasso Carrara Bella (H)
w/ Stainless Steel
MB1604-COMPH0





GENTLE BODY WASH
milk + honey







Architetto Modulo Ash Gray (H&P)

MB1809-MODU00



Architetto Modulo Calacatta (H&P)

MB1203-MODU00



Architetto Modulo Calacatta (H) w/ Brass

MB1203-MODUH0



Architetto Modulo Carrara Bella (H&P)

MB1604-MODU00



Architetto Modulo Carrara Bella (H)

w/ Stainless Steel

MB1604-MODUH0



CONVERSION CHART

PROFILE	SIZE
Angolo	8" x 8" = .444 sqft
Compasso	8" x 8" = .444 sqft
Modulo	12" x 12" = 1.0 sqft

APPLICATIONS – ARCHITETTO MOSAICS WITHOUT METAL

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL
Yes	Yes	Yes	No	Yes, if sealed properly	Yes, if sealed properly	No

APPLICATIONS – ARCHITETTO MOSAICS WITH BRASS*

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL
Yes	Yes	Yes	No	No	No	No

APPLICATIONS – ARCHITETTO MOSAICS WITH STAINLESS STEEL*

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL
Yes	Yes	Yes	No	No	Yes, if sealed properly	No

TECHNICAL DATA

FEATURES	RESULT
Heat Resistance	Heat not to exceed 293° F
Traffic	Standard Commercial
DCOF (ANSI A137.1)	>.42

Modulo Calacatta (H&P) and Modulo Calacatta (H) with Brass were used as representative samples to determine the dynamic coefficient of friction (DCOF) for the Architetto collection.

Epoxy grout should be used when installing Architetto mosaics with metal. For detailed installation guidelines, visit akdo.com.

*As a natural material, brass is prone to oxidation; a chemical reaction that occurs over time from exposure to air. Both stainless steel and brass may scratch when used as floor covering.

Product Design
Consultant

Gensler

Gensler is a global architecture, design, and planning firm with 49 locations and more than 6,000 professionals networked across Asia, Europe, Australia, the Middle East, and the Americas. Founded in 1965, the firm serves more than 3,300 active clients in virtually every industry. Gensler designers strive to make the places people live, work, and play more inspiring, more resilient, and more impactful. As product designers, the firm draws on its vast knowledge of new materials, the latest technologies, and evolving workplace trends to enhance visual appeal, performance, and end user experience.

AKDO

1435 State Street
Bridgeport, CT 06605
1.800.811.2536
203.336.5199 (o)
203.336.0603 (f)

AKDO NYC

22 West 21st Street
New York, NY 10010
1.800.811.2536
212.485.0448 (o)
212.485.0449 (f)

AKDO Pacific

3445 Arden Road
Hayward, CA 94545
1.888.909.2536
510.785.2536 (o)
510.785.0895 (f)

akdo.com

