

## ESSENTIAL CERAMIC 2" X 8" STORM GRAY (G) *Ceramic*



PART NUMBER  
CR2093-0208G0

PROFILE  
TILE

AVAILABILITY  
IN STOCK

VARIATION  
LOW

DIMENSIONS  
1.97" x 7.87" = .108 sqft

GROUT JOINT  
1/16"

THICKNESS  
3/8"

SEALER  
NOT REQUIRED, GROUT MAY REQUIRE SEALING

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	Yes	Yes	No	

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	Compliant	UNE-EN-ISO-10545-3
Modulus of rupture and breaking strength	Compliant	UNE-EN-ISO-10545-4
Thermal Shock Resistance	Resistant	UNE-EN-ISO-10545-9
Crazing resistance	Resistant	UNE-EN-ISO-10545-11
Stain resistance	Class 5	UNE-EN-ISO-10545-14

DUE TO THE INHERENT CHARACTERISTICS OF CERAMIC, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).