


ORIGIN 10 1/2" X 1/2" LINER HYDRANGEA (G) Ceramic

	PART NUMBER	PROFILE	AVAILABILITY
	CR2504-LN10G0	TRIM	IN STOCK
	GROUT JOINT	THICKNESS	ORIGIN
	1/16"	3/8"	Spain
NOTES			
Due to the inherent characteristics of ceramic, there may be variations in color, movement and texture from lot to lot.			

APPLICATION AREA

EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR	SHOWER
No	No	Yes	Yes	No	Wall Only	Wall Only, Including Steam

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Bond Strength - EN 14411	> 1 N/mm2	Breaking Strength - ISO 10545-4	Compliant
Coefficient of Thermal Linear Expansion - ISO 10545-8	< 7*10-6 1/C-1	Crazing Resistance - ISO 10545-11	Resistant
Bending Resistance - ISO 10545-4	Compliant	Reaction to Fire - N/A	A1
Reaction to Fire - EN 13501-1	Compliant	Reaction to Fire - EN 14411	Compliant
Regularity of Length & Width - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	GA
Resistance to Swimming Pool Salts - ISO 10545-13	GA	Surface Flatness - ISO 10545-2	Compliant
Water Absorption - ISO 10545-3	Compliant		