

MODERN LINER POWDER (C) *Glass*



PART NUMBER	PROFILE	AVAILABILITY
GL1771-ML12C0	TRIM	REGULAR STOCK
GROUT JOINT	DIMENSIONS	THICKNESS
1/8"	.38" x 11.75" = .98 lft	5/16"

NOTES

Due to the inherent characteristics of glass there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND	INTERIOR
Yes	No	Yes	Yes	Yes	Yes	YES - Heat not to exceed 1472°F	YES - Heat not to exceed 1472°F	Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

0.28