

TRAPEZOID HERITAGE ASH *Porcelain*



PART NUMBER
PO1900-TRAP00

AVAILABILITY
AVAILABLE UPON REQUEST

DIMENSIONS
1pc=0.247sqft

THICKNESS
3/8"

VARIATION
LOW

GROUT JOINT
1/8"

SEALER
NOT REQUIRED, GROUT MAY REQUIRE SEALING

ENVIRONMENTS

| WALL | FLOOR | INTERIOR | EXTERIOR FREEZE/THAW | STEAM SHOWER | WET AREA | POOL | REPEAT |
|------|-------|----------|-------------------------|-----------------|-------------|------|--------|
| Yes | Yes | Yes | Yes | Yes | Yes | Yes | |

TECHNICAL DATA

| FEATURES | SPECIFICATION | STANDARD |
|--|--|---------------------|
| Water absorption | UNI-EN ISO 10545-3 $\leq 0.5\%$ Compliant | UNE-EN-ISO-10545-3 |
| Modulus of rupture and breaking strength | UNI-EN ISO 10545-4 > 35 N/mm ² (≥ 7.5 mm) Compliant | UNE-EN-ISO-10545-4 |
| Thermal Shock Resistance | UNI-EN 10545-9 Resistant | UNE-EN-ISO-10545-9 |
| Crazing resistance | UNI-EN ISO 10545-11 Resistant | UNE-EN-ISO-10545-11 |
| Frost resistance | UNI-EN ISO 10545-12 Resistant | UNE-EN-ISO-10545-12 |
| Chemical resistance | UNI-EN ISO 10545-13 Guaranteed (GA GLA GHA) | UNE-EN-ISO-10545-13 |
| Stain resistance | UNI-EN ISO 10545-14 CLASS 5 | UNE-EN-ISO-10545-14 |
| DCOF | $>.42$ (actual score .68) | ANSI A137.1 |
| TRAFFIC | Light Commercial | NA |

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit akdo.com.