

HERITAGE HEXAGON BLACK (M) *Porcelain*



PART NUMBER
PO1902-HEXA00

GROUT JOINT
1/8"

ORIGIN
Italy

NOTES
Available nationwide.

PROFILE
TILE

DIMENSIONS
10.60" x 9.00" = .494 sqft

AVAILABILITY
IN STOCK

THICKNESS
3/8"

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Light Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-7	Class 3	Slip Resistance - UNI ENV 12633	Class 1
Barefoot Ramp Test - DIN 51097	Class A	Breaking Strength - ISO 10545-4	> 1300 N (P 7.5mm) > 700 N (c 7.5mm) Compliant
Chemical Resistance - ISO 10545-13	Guaranteed (GA GLA GHA)	Coefficient of Thermal Linear Expansion - ISO 10545-8	Test Method Available
Crazing Resistance - ISO 10545-11	Resistant	Frost Resistance - ISO 10545-12	Resistant
Bending Resistance - ISO 10545-4	> 35 N/mm ² (P 7.5mm) Compliant	Scratch Resistance (MOHS) - EN 101	35
Reaction to Fire - EN 13501-1	A1 FL-A1	Regularity of Length & Width - ISO 10545-2	± 0.6% Compliant
Regularity of Rectangularity - ISO 10545-2	± 0.5% Compliant	Regularity of Straightness of Sides - ISO 10545-2	± 0.5% Compliant
Surface Flatness - ISO 10545-2	± 0.5%	Water Absorption - ISO 10545-3	² 0.5% Compliant
Colour Resistance to Light - DIN 510914	Resistant	Lead and Cadmium Given Off - UNI-EN ISO 10545-15	Test Method Available

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

> 0.42 (actual score .68)