

HERITAGE HEXAGON HIGHLAND PATTERN (M) *Porcelain*



PART NUMBER
PO1903-HEXA00

PROFILE
TILE

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
10.60" x 9.00" = .494 sqft

THICKNESS
3/8"

ORIGIN
Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Light Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

Slip Resistance - UNI ENV 12633

Breaking Strength - ISO 10545-4

Coefficient of Thermal Linear Expansion - ISO 10545-8

Frost Resistance - ISO 10545-12

Scratch Resistance (MOHS) - EN 101

Regularity of Length & Width - ISO 10545-2

Regularity of Straightness of Sides - ISO 10545-2

Water Absorption - ISO 10545-3

Lead and Cadmium Given Off - UNI-EN ISO 10545-15

SPECIFICATION

Class 1

> 1300 N (≠ 7.5mm) > 700 N (≠ 7.5mm) Compliant

Test Method Available

Resistant

35

± 0.6% Compliant

± 0.5% Compliant

± 0.5% Compliant

Test Method Available

FEATURES & STANDARD

Barefoot Ramp Test - DIN 51097

Chemical Resistance - ISO 10545-13

Crazing Resistance - ISO 10545-11

Bending Resistance - ISO 10545-4

Reaction to Fire - EN 13501-1

Regularity of Rectangularity - ISO 10545-2

Surface Flatness - ISO 10545-2

Colour Resistance to Light - DIN 510914

SPECIFICATION

Class A

Guaranteed (GA GIA GHA)

Resistant

> 35 N/mm² (≠ 7.5mm) Compliant

A1 FL-A1

± 0.5% Compliant

± 0.5%

Resistant

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

> 0.42 (actual score .68)