

PASSAGE EVOLUTION BLACK (M) Porcelain



PART NUMBER
PO2287-EVOL00

PROFILE **TILE** AVAILABILITY IN STOCK

GROUT JOINT

DIMENSIONS

THICKNESS

1/8"

 $7.28'' \times 7.28'' = .368 \text{ sqft}$

3/8"

ORIGIN

Spain

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Residential	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

				_
FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION	
Chemical Resistance - ISO 10545-13	GLA	Crazing Resistance - ISO 10545-11	Pass	
Frost Resistance - ISO 10545-12	Pass	Bending Resistance - ISO 10545-4	Minimum 35 N/mm2 Individual Minimum 32 N	/mm2
Regularity of Length & Width - ISO 10545-2	186 +/- 0.6 x 186 +/-0.6 mm x 10 mm	Resistance to Household Chemicals - ISO 10545-13	GA	
Resistance to Swimming Pool Salts - ISO 10545-13	GA	Water Absorption - ISO 10545-3	Eb ² 0.5%	TECHNIC
EEATLIBES & STANIDARD	SDECIEIC ATION I			

FEATURES & STANDARD

SPECIFICATION

DCOF - ANSI A. 137. 1

> 0.42