

PLAZA NUEVA MIRAMAR GRAY (M) Porcelain



PART NUMBER

PROFILE TILE

AVAILABILITY IN STOCK

GROUT JOINT

PO2573-HEXA00

DIMENSIONS

THICKNESS

1/16"

 $7.87'' \times 9.06'' = .377 \text{ sqft}$

3/8"

ORIGIN

Spain

NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWE	WET R AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Residential and Light Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information

TECHNICAL DATA

Group 3	TECHNICAL DATA	LD - 0.3%	
GA	vivdier Absorption - 150 10343-3	LD - 0.5%	
♠ A	\A/ \A/	Eb ² 0.5%	
Resistant	Resistance to Household Chemicals - ISO 10545-13	GA	
GLA	Crazing Resistance - ISO 10545-11	Resistant	
SPECIFICATION	FEATURES & STANDARD	SPECIFICATION	
	GLA Resistant	GLA Crazing Resistance - ISO 10545-11	

DCOF - ANSI A. 137. 1

> 0.42

LEED

MR MR

Low Emitting Materials Material Ingredient ReportingMaterial Ingredient Optimization

No VOCs emission

Red List Free

Compliant with the Restrictions of Reach and are free of the SVHC listed on the candidate list.