

## SIO SOLID BLACK HEX (M) *Porcelain*



PART NUMBER  
PO2540-HEXAM0

GROUT JOINT  
1/16"

ORIGIN  
Spain

### NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

PROFILE  
TILE

DIMENSIONS  
7.87" x 9.06" = .377 sqft

AVAILABILITY  
IN STOCK

THICKNESS  
3/8"

### APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Light Residential	Yes	Yes	Yes	Yes	Yes	Yes

### INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

### TECHNICAL DATA

#### FEATURES & STANDARD

Chemical Resistance - ISO 10545-13

Frost Resistance - ISO 10545-12

Resistance to Swimming Pool Salts - ISO 10545-13

Pei Rating

#### SPECIFICATION

GLA

Resistant

GA

Group 2

#### FEATURES & STANDARD

Crazing Resistance - ISO 10545-11

Resistance to Household Chemicals - ISO 10545-13

Water Absorption - ISO 10545-3

#### SPECIFICATION

Resistant

GA

Eb <sup>2</sup> 0.5%

### TECHNICAL DATA

#### FEATURES & STANDARD

DCOF - ANSI A.137.1

#### SPECIFICATION

> 0.42

### LEED

EQ	MR	MR
Low Emitting Materials	Material Ingredient Reporting	Material Ingredient Optimization

No VOCs emission

Red List Free

Compliant with the Restrictions of Reach and are free of the SVHC listed on the candidate list.