# AKDO

## SIO STRATA BEIGE HEX (M) Porcelain



| Part Number     | PROFILE                  | availability  |
|-----------------|--------------------------|---------------|
| PO2546-Hexam0   | TILE                     | Regular Stock |
| GROUT JOINT     | DIMENSIONS               | THICKNESS     |
| 1/16"           | 7.87" x 9.06" = .37 sqft | 3/8"          |
| ORIGIN<br>Spain |                          |               |
| NOTES           |                          |               |

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

#### APPLICATION AREA

| WALL | FLOOR | TRAFFIC                             | EXTERIOR | STEAM<br>SHOWER | WET<br>R AREA | POOL | BACKSPLASH | FIREPLACE<br>SURROUND |
|------|-------|-------------------------------------|----------|-----------------|---------------|------|------------|-----------------------|
| Yes  | Yes   | Residential and<br>Light Commercial | Yes      | Yes             | Yes           | Yes  | Yes        | Yes                   |

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

#### **TECHNICAL DATA**

| FEATURES & STANDARD                              | SPECIFICATION | FEATURES & STANDARD                              | Specification        |
|--|---------------|--|----------------------|
| Chemical Resistance - ISO 10545-13               | GLA           | Crazing Resistance - ISO 10545-11                | Resistant            |
| Frost Resistance - ISO 10545-12                  | Resistant     | Resistance to Household Chemicals - ISO 10545-13 | GA                   |
| Resistance to Swimming Pool Salts - ISO 10545-13 | GA            | Water Absorption - ISO 10545-3                   | Eb <sup>2</sup> 0.5% |
| Pei Rating                                       | Group 3       |  |                      |
| DCOF - ANSI A. 137. 1                            |               |  |                      |
|  | > 0.42        |  |                      |

LEED

| EQ                     | MR                           | MR  |
|------------------------|------------------------------|---|
| Low Emitting Materials | Material Ingredient Reportin | IgMaterial Ingredient Optimization  |
| No VOCs emission       | Red List Free                | Compliant with the Restrictions of Reach and are free of the SVHC listed on the candidate list. |

### akdo.com