AKDO®

SIO STRATA BLACK HEX (M) *Porcelain*



PART NUMBER	PROFILE	AVAILABILITY
PO2537-HEXAM0	TILE	REGULAR STOCK
GROUT JOINT	**DIMENSIONS**	**THICKNESS**
1/16"	7.87" x 9.06" = .37 sqft	3/8"
ORIGIN		
Spain		

NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Light Residential	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR
Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Chemical Resistance - ISO 10545-13	GLA	Crazing Resistance - ISO 10545-11	Resistant
Frost Resistance - ISO 10545-12	Resistant	Resistance to Household Chemicals - ISO 10545-13	GA
Resistance to Swimming Pool Salts - ISO 10545-13	GA	Water Absorption - ISO 10545-3	Eb ² 0.5%
Pei Rating	Group 2		
DCOF - ANSI A.137.1	> 0.42		

LEED

EQ	MR	MR
Low Emitting Materials	Material Ingredient Reporting	Material Ingredient Optimization
No VOCs emission	Red List Free	Compliant with the Restrictions of Reach and are free of the SVHC listed on the candidate list.