

## AMALFI 16" X 32" TERRA (M) *Porcelain*



PART NUMBER  
PO2659-1632M0

PROFILE  
TILE

AVAILABILITY  
REGULAR STOCK

GROUT JOINT  
1/16"

DIMENSIONS  
15.748" x 31.496" = 3.444 sqft

THICKNESS  
3/8"

ORIGIN  
Italy

### NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

### APPLICATION AREA

| WALL | FLOOR | TRAFFIC    | EXTERIOR | STEAM<br>SHOWER | WET<br>AREA | POOL | BACKSPLASH | FIREPLACE<br>SURROUND |
|------|-------|------------|----------|-----------------|-------------|------|------------|-----------------------|
| Yes  | Yes   | Commercial | Yes      | Yes             | Yes         | Yes  | Yes        | Yes                   |

### INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

### TECHNICAL DATA

| FEATURES & STANDARD                              | SPECIFICATION           | FEATURES & STANDARD                                   | SPECIFICATION |
|--|-------------------------|---|---------------|
| Abrasion Resistance - ISO 10545-6                | Compliant               | Coefficient of Thermal Linear Expansion - ISO 10545-8 | ≤ 7 10-6•C-1  |
| DCOF - B.C.R.A. Rep. CEC-81                      | Dry > 0.40 / Wet > 0.40 | Frost Resistance - ISO 10545-12                       | Compliant     |
| Coefficient of Restitution - ISO-10545-5         | Compliant               | Bending Resistance - ISO 10545-4                      | Compliant     |
| Moisture Expansion - ISO 10545-10                | ≤ 0.01 %                | Regularity of Length & Width - ISO 10545-2            | Compliant     |
| Resistance to Household Chemicals - ISO 10545-13 | A                       | Resistance To Staining - ISO 10545-14                 | Class 5       |
| Resistance to Swimming Pool Salts - ISO 10545-13 | A                       | Slip Resistance (Ramp Test) - DIN 51130               | R10           |
| Thermal Shock Resistance - ISO 10545-9           | Compliant               | Water Absorption - ISO 10545-3                        | 0.2%          |
| DCOF – ANSI A326.3:2019                          | > 0.42 Wet              |   |               |

### LEED

#### MR

#### Environmental Product Declaration

Available industry-wide Environmental Product Declaration (EPD)