

CONCRETE JUNGLE 2" X 2" FACTORY (SOFT) *Porcelain*



PART NUMBER
PO2523-M002ST

PROFILE
MOSAIC

AVAILABILITY
REGULAR STOCK

DIMENSIONS
11.81" x 11.81" = .970 sqft

THICKNESS
10mm

ORIGIN
Italy

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Standard Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	145 mm ³	Breaking Strength - ISO 10545-4	Thick. 10mm: 2.500 N
Chemical Resistance - ISO 10545-13	LA, HA Resistant	Coefficient of Thermal Linear Expansion - ISO 10545-8	$\alpha < 10^{-6} \text{ } ^\circ\text{C}^{-1}$
Shade Variation - ANSI A 137.1	V3	Frost Resistance - ISO 10545-12	Resistant
Bending Resistance - ISO 10545-4	50 N/mm ²	Fire Reaction - EN 9239-1	Class A1fl (floor)
Fire Reaction - EN 13823	Class A1 (wall)	Regularity of Length & Width - ISO 10545-2	Compliant
Regularity of Rectangularity - ISO 10545-2	Compliant	Regularity of Straightness of Sides - ISO 10545-2	Compliant
Slip Resistance - ANSI A326.3	DCOF ³ 0.42	Water Absorption - ISO 10545-3	0.05%
Thermal Conductivity - EN 12524	$\lambda = 1.3 \text{ W/m } ^\circ\text{K}$		
DCOF - ANSI A.137.1	>0.42		

LEED

MR	MR	EQ	ID
Recycled Content	Environmental Product Declaration	Low Emitting Materials	Innovation & Design
40% Pre-Consumer Recycled Material	Available industry-wide Environmental Product Declaration (EPD)	No VOCs Emission	Certificate GOLD Greenguard