


## 24" X 24" WIDE LEAD (TEXTURED) *Porcelain*



PART NUMBER  
**PO2132-2424T0**

AVAILABILITY  
**AVAILABLE UPON REQUEST**

DIMENSIONS  
**1pc=60cm x 60cm=3.875 sqft**

THICKNESS  
**3/8"**

PROFILE  
**TILE**

VARIATION  
**V2**

GROUT JOINT  
**1/16"**

SEALER  
**SEALING NOT REQUIRED, GROUT MAY REQUIRE SEALING**

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	0.20%	UNE-EN-ISO-10545-3
Modulus of rupture and breaking strength	UNI EN ISO 10545/4 S □ 1300 N Compliant	UNE-EN-ISO-10545-4
Thermal Shock Resistance	UNI EN ISO 10545/9 Compliant	UNE-EN-ISO-10545-9
Frost resistance	UNI EN ISO 10545/12 Compliant	UNE-EN-ISO-10545-12
Chemical resistance	RESISTANT	UNE-EN-ISO-10545-13
Stain resistance	UNI EN ISO 10545/14 GL □ 3 See inside	UNE-EN-ISO-10545-14
DCOF	>0.42	ANSI A137.1
TRAFFIC	Heavy Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).