

#### WIDE 24" X 24" LEAD (M) Porcelain



PART NUMBER PO2132-2424M0

GROUT JOINT 1/16"

ORIGIN Italy

NOTES Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

PROFILE

DIMENSIONS

 $23.64'' \times 23.64'' = 3.87 \text{ sqft}$ 

TILE

AVAILABILITY

IN STOCK

THICKNESS

3/8"

# APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWE	WET R AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information

### TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION	
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant	
Coefficient of Thermal Linear Expansion - ISO 10545-8	<sup>2</sup> 7_MK-1	Coefficient of Friction - B.C.R.A. Rep. CEC/81	Asciutto > 0.40, Bagnato > 0.40	
Frost Resistance - ISO 10545-12	Compliant	Impact Resistance - ISO 10545-5	Compliant	
Bending Resistance - ISO 10545-4	Compliant	Reaction to Fire - EN 13501-1	Alfl	
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant	
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	Compliant	
Resistance to Swimming Pool Salts - ISO 10545-13	Compliant	Surface Flatness - ISO 10545-2	Compliant	
Water Absorption - ISO 10545-3	0.2%	TECHNICAL DATA		

FEATURES & STANDARD

**SPECIFICATION** 

DCOF - ANSI A. 137. 1

> 0.42 Wet

# LEED

EQ112 Low<sub>1</sub>Emitting Materials Recycled Content akdo.com

Zero Emissions V.O.C. 20% pre-consumer recycled material

COMMERCIAL · HOSPITALITY · RESIDENTIAL