AKDO

WIDE 24'' X 48'' OLIVE (M)



Porcelain

PART NUMBER	PROFILE	AVAILABILITY
PO2133-2448M0	TILE	AVAILABLE ON REQUEST
GROUT JOINT	DIMENSIONS	THICKNESS
1/16"	23.62'' x 47.24'' = 7.750 sqft	3/8"
ORIGIN Italy		

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

ATION FEATURES & STANDARD Breaking Strength - ISO 10545-4 Coefficient of Friction - B.C.R.A. Rep. CEC/81	SPECIFICATION Compliant
0 0	Compliant
Coefficient of Friction - B.C.R.A. Rep. CEC/81	
	Asciutto > 0.40, Bagnato > 0.40
Impact Resistance - ISO 10545-5	Compliant
Reaction to Fire - EN 13501-1	Alfi
Regularity of Rectangularity - ISO 10545-2	Compliant
Resistance to Household Chemicals - ISO 1054	45-13 Compliant
Surface Flatness - ISO 10545-2	Compliant

FEATURES & STANDARD

SPECIFICATION

DCOF - ANSI A.137.1

> 0.42 Wet

LEED

EQ112		MR	
Low Emitting Materials		Recycled Content	
Zero Emissions	V.O.C.	20% pre-consumer recycled material	