

## WIDE 12" X 24" STEEL (TEXTURED) *Porcelain*



PART NUMBER  
PO2134-1224T1

PROFILE  
TILE

AVAILABILITY  
IN STOCK

GROUT JOINT  
1/16"

DIMENSIONS  
11.81" x 23.62" = 1.94 sqft

THICKNESS  
3/8"

NOTES  
Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

### APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER AREA	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

### TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant
Coefficient of Thermal Linear Expansion - ISO 10545-8	≤7_MK-1	Coefficient of Friction - B.C.R.A. Rep. CEC/81	Asciutto > 0.40, Bagnato > 0.40
DCOF - ANSI A.137.1	> 0.42 Wet	Frost Resistance - ISO 10545-12	Compliant
Impact Resistance - ISO 10545-5	Compliant	Bending Resistance - ISO 10545-4	Compliant
Reaction to Fire - EN 13501-1	A1fl	Regularity of Length & Width - ISO 10545-2	Compliant
Regularity of Rectangularity - ISO 10545-2	Compliant	Regularity of Straightness of Sides - ISO 10545-2	Compliant
Resistance to Household Chemicals - ISO 10545-13	Compliant	Resistance to Swimming Pool Salts - ISO 10545-13	Compliant
Surface Flatness - ISO 10545-2	Compliant	Water Absorption - ISO 10545-3	0.2%

### LEED

EQ112	MR
Low-Emitting Materials	Recycled Content
Zero Emissions	20% pre-consumer recycled material