AKDO

WIDE 12" X 24" STEEL (TEXTURED) Porcelain



) Porceium

PART NUMBER PO2134-1224T1

GROUT JOINT

| PROFILE TILE | availability In stock |
|---|--------------------------|
| DIMENSIONS 11.81'' x 23.62'' = 1.94 sqft | THICKNESS 3/8" |

NOTES

ORIGIN Italy

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

| WALL | FLOOR | TRAFFIC | EXTERIOR | STEAM SHOWER | WET AREA | POOL | BACKSPLASH | FIREPLACE SURROUND |
|------|-------|---------------------|----------|-----------------|-------------|------|------------|-----------------------|
| Yes | Yes | Heavy Commercial | Yes | Yes | Yes | Yes | Yes | Yes |

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

| SPECIFICATION | FEATURES & STANDARD | SPECIFICATION |
|---------------|---|--|
| Compliant | Breaking Strength - ISO 10545-4 | Compliant |
| 27_MK-1 | Coefficient of Friction - B.C.R.A. Rep. CEC/81 | Asciutto > 0.40, Bagnato > 0.40 |
| Compliant | Impact Resistance - ISO 10545-5 | Compliant |
| Compliant | Reaction to Fire - EN 13501-1 | Alf |
| Compliant | Regularity of Rectangularity - ISO 10545-2 | Compliant |
| Compliant | Resistance to Household Chemicals - ISO 10545-13 | Compliant |
| Compliant | Surface Flatness - ISO 10545-2 | Compliant |
| 0.2% | TECHNICAL DATA | |
| | Compliant 27_MK-1 Compliant Compliant Compliant Compliant Compliant | CompliantBreaking Strength - ISO 10545-427_MK-1Coefficient of Friction - B.C.R.A. Rep. CEC/81CompliantImpact Resistance - ISO 10545-5CompliantReaction to Fire - EN 13501-1CompliantRegularity of Rectangularity - ISO 10545-2CompliantResistance to Household Chemicals - ISO 10545-13CompliantSurface Flatness - ISO 10545-2 |

FEATURES & STANDARD

SPECIFICATION

DCOF - ANSI A.137.1

> 0.42 Wet

LEED

| EQ112 | | MR | |
|------------------------|--------|------------------------------------|--|
| Low_Emitting Materials | | Recycled Content | |
| Zero Emissions | V.O.C. | 20% pre-consumer recycled material | |