

PENNY ROUNDS TRANQUIL (G) Porcelain



PART NUMBER
PO2513-PENYG0

PROFILE MOSAIC AVAILABILITY
IN STOCK

DIMENSIONS

 $11.57" \times 12.40" = .996 \text{ sqft}$

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installation from more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Breaking Strength - ISO 10545-4	812	Crazing Resistance - ISO 10545-11	Pass
Regularity of Rectangularity - ISO 10545-2	-0.12~+0.11	Regularity of Straightness of Sides - ISO 10545-2	-0.12~+0.11
Surface Quality - ISO 10545-2	Conformed	Resistance to Household Chemicals - ISO 10545-13	Class GA
Resistance to Swimming Pool Salts - ISO 10545-13	Class GA	Modulus of Rupture - ISO 10545-4	53 / 50~56