

## ELITE 24" X 24" DARK BROWN (N) *Porcelain*



PART NUMBER  
**PO2680-2424N0**

PROFILE  
**TILE**

AVAILABILITY  
**REGULAR STOCK**

GROUT JOINT  
**1/16"**

DIMENSIONS  
**23.62" x 23.62" = 3.875 sqft**

THICKNESS  
**10mm**

ORIGIN  
**Italy**

### NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

### APPLICATION AREA

| WALL | FLOOR | TRAFFIC          | EXTERIOR | STEAM SHOWER | WET AREA | POOL | BACKSPASH | FIREPLACE SURROUND |
|------|-------|------------------|----------|--------------|----------|------|-----------|--------------------|
| Yes  | Yes   | Heavy Commercial | Yes      | Yes          | Yes      | Yes  | Yes       | Yes                |

### INTERIOR

Yes

### TECHNICAL DATA

| FEATURES & STANDARD   | SPECIFICATION                                 | FEATURES & STANDARD  | SPECIFICATION        |
|---|---|--|----------------------|
| Abrasion Resistance - ISO 10545-6                             | ≤ 175mm <sup>3</sup>                          | Barefoot Ramp Test - DIN 51097                                 | A+B                  |
| Bond Strength - EN 1348                                       | ≥ 1.0 N/mm <sup>2</sup> (Class C2 - EN 12004) | Breaking Strength - ISO 10545-4                                | S ≥ 1300 N           |
| Coefficient of Thermal Linear Expansion - ISO 10545-8         | ≤ 7MK-1                                       | Coefficient of Friction - B.C.R.A. Rep. CEC/81                 | >0.42 Dry, >0.42 Wet |
| Frost Resistance - ISO 10545-12                               | Resistant                                     | Impact Resistance - ISO 10545-5                                | ≥ 0.55               |
| Bending Resistance - ISO 10545-4                              | ≥ 1300 N                                      | Moisture Expansion - ISO 10545-10                              | ≤ 0.01% (0.1mm/m)    |
| Reaction to Fire - N/A  | A1 - A1fl                                     | Regularity of length & Width - ISO 10545-2                     | Compliant            |
| Regularity of Rectangularity - ISO 10545-2                    | Compliant                                     | Regularity of Straightness of Sides - ISO 10545-2              | Compliant            |
| Regularity of Thickness - ISO 10545-2                         | Compliant                                     | Resistance to Household Chemicals - ISO 10545-13               | A                    |
| Resistance to Swimming Pool Salts - ISO 10545-13              | A   | Booted Ramp Test - DIN 51130                                   | R9 NATURAL           |
| Surface Flatness - ISO 10545-2                                | Compliant                                     | Thermal Shock Resistance - ISO 10545-9                         | Resistant            |
| Water Absorption - ASTM C373                                  | ≤ 0.5%  | Water Absorption - ISO 10545-3                                 | ≤ 0.1%               |
| Pendulum Friction Test - AS/NZS 4586                          | Class P3                                      | Pendulum Friction Test - UNE-ENV 12633 (CEN/TS 16165, Annex C) | Class C2             |
| Pendulum Friction Test - BS 7976-2002 (CEN/TS 16165, Annex C) | ≥ 36Dry, ≥ 36Wet                              |  |                      |
| DCOF - ANSI A.137.1   | > 0.42 Wet                                    |  |                      |