


ELITE 2"X 2" DARK BROWN (G) *Porcelain*



PART NUMBER
PO2680-M002G0

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/16"

DIMENSIONS
11.81" x 11.81" = 0.97 sqft

THICKNESS
10mm

ORIGIN
Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

| WALL | FLOOR | TRAFFIC | EXTERIOR FREEZE/THAW | STEAM SHOWER | WET AREA | POOL | BACKSPLASH | FIREPLACE SURROUND |
|------|-------|---------------------|-------------------------|-----------------|-------------|------|------------|-----------------------|
| Yes | Yes | Heavy Commercial | Yes | Yes | Yes | Yes | Yes | Yes |

TECHNICAL DATA

| FEATURES & STANDARD | SPECIFICATION | FEATURES & STANDARD | SPECIFICATION |
|--|---|---|----------------------|
| Abrasion Resistance - ISO 10545-6 | ≤ 175mm ³ | Barefoot Ramp Test - DIN 51097 | A+B |
| Bond Strength - EN 1348 | ≥ 1.0 N/mm ² (Class C2 - EN 12004) | Breaking Strength - ISO 10545-4 | S ≥ 1300 N |
| Coefficient of Thermal Linear Expansion - ISO 10545-8 | ≤ 7MK-1 | Coefficient of Friction - B.C.R.A. Rep. CEC/81 | >0.42 Dry, >0.42 Wet |
| DCOF - ANSI A.137.1 | > 0.42 Wet | Frost Resistance - ISO 10545-12 | Resistant |
| Impact Resistance - ISO 10545-5 | ≥ 0.55 | Bending Resistance - ISO 10545-4 | ≥ 1300 N |
| Moisture Expansion - ISO 10545-10 | ≤ 0.01% (0.1 mm/m) | Reaction to Fire - N/A | A1 - A1fl |
| Regularity of Length & Width - ISO 10545-2 | Compliant | Regularity of Rectangularity - ISO 10545-2 | Compliant |
| Regularity of Straightness of Sides - ISO 10545-2 | Compliant | Regularity of Thickness - ISO 10545-2 | Compliant |
| Resistance to Household Chemicals - ISO 10545-13 | A | Resistance to Swimming Pool Salts - ISO 10545-13 | A |
| Booted Ramp Test - DIN 51130 | R9 NATURAL | Surface Flatness - ISO 10545-2 | Compliant |
| Thermal Shock Resistance - ISO 10545-9 | Resistant | Water Absorption - ASTM C373 | ≤ 0.5% |
| Water Absorption - ISO 10545-3 | ≤ 0.1% | Pendulum Friction Test - AS/NZS 4586 | Class P3 |
| Pendulum Friction Test - UNE-ENV 12633 [CEN/TS 16165, Annex C] | Class C2 | Pendulum Friction Test - BS 7976-2002 [CEN/TS 16165, Annex C] | ≥ 36Dry, ≥ 36Wet |