

## ELITE 2"X 2" STATUARIO (G) *Porcelain*



PART NUMBER  
**PO2675-M002G0**

PROFILE  
**MOSAIC**

AVAILABILITY  
**REGULAR STOCK**

GROUT JOINT  
**1/16"**

DIMENSIONS  
**11.81" x 11.81" = 0.97 sqft**

THICKNESS  
**10mm**

ORIGIN  
**Italy**

### NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

### APPLICATION AREA

| WALL | FLOOR | TRAFFIC    | EXTERIOR | STEAM<br>SHOWER | WET<br>AREA | POOL | BACKSPLASH | FIREPLACE<br>SURROUND |
|------|-------|------------|----------|-----------------|-------------|------|------------|-----------------------|
| Yes  | Yes   | Commercial | Yes      | Yes             | Yes         | Yes  | Yes        | Yes                   |

### INTERIOR

Yes

### TECHNICAL DATA

| FEATURES & STANDARD  | SPECIFICATION                                 | FEATURES & STANDARD   | SPECIFICATION        |
|--|---|---|----------------------|
| Abrasion Resistance - ISO 10545-6                              | ≤ 175mm <sup>3</sup>                          | Barefoot Ramp Test - DIN 51097                                | A+B                  |
| Bond Strength - EN 1348  | ≥ 1.0 N/mm <sup>2</sup> (Class C2 - EN 12004) | Breaking Strength - ISO 10545-4                               | S ≥ 1300 N           |
| Coefficient of Thermal Linear Expansion - ISO 10545-8          | ≤ 7MK-1                                       | Coefficient of Friction - B.C.R.A. Rep. CEC/81                | >0.42 Dry, >0.42 Wet |
| Frost Resistance - ISO 10545-12                                | Resistant                                     | Impact Resistance - ISO 10545-5                               | ≥ 0.55               |
| Bending Resistance - ISO 10545-4                               | ≥ 1300 N                                      | Reaction to Fire - N/A  | A1 - A1fl            |
| Regularity of Length & Width - ISO 10545-2                     | Compliant                                     | Regularity of Rectangularity - ISO 10545-2                    | Compliant            |
| Regularity of Straightness of Sides - ISO 10545-2              | Compliant                                     | Regularity of Thickness - ISO 10545-2                         | Compliant            |
| Resistance to Household Chemicals - ISO 10545-13               | A   | Resistance to Swimming Pool Salts - ISO 10545-13              | A                    |
| Booted Ramp Test - DIN 51130                                   | R9 NATURAL                                    | Surface Flatness - ISO 10545-2                                | Compliant            |
| Thermal Shock Resistance - ISO 10545-9                         | Resistant                                     | Water Absorption - ASTM C373                                  | ≤ 0.5%               |
| Water Absorption - ISO 10545-3                                 | ≤ 0.1%  | Pendulum Friction Test - AS/NZS 4586                          | Class P3             |
| Pendulum Friction Test - UNE-ENV 12633 (CEN/TS 16165, Annex C) | Class C2                                      | Pendulum Friction Test - BS 7976-2002 (CEN/TS 16165, Annex C) | ≥ 36Dry, ≥ 36Wet     |
| DCOF - ANSI A.137.1  | > 0.42 Wet                                    |   |                      |