

GAJA GRAY 2X2 MOSAIC (T) *Porcelain*



PART NUMBER
PO2412-0202T0

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

DIMENSIONS
11.81" x 11.81" = .97 sqft

ORIGIN
Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

| WALL | FLOOR | TRAFFIC | EXTERIOR | STEAM SHOWER | WET AREA | POOL | BACKSPASH | FIREPLACE SURROUND |
|------|-------|---------------------|----------|-----------------|-------------|------|-----------|-----------------------|
| Yes | Yes | Heavy Commercial | Yes | Yes | Yes | Yes | Yes | Yes |

INTERIOR

Yes

TECHNICAL DATA

| FEATURES & STANDARD | SPECIFICATION | FEATURES & STANDARD | SPECIFICATION |
|---|-------------------------------------|--|----------------------------------|
| Abrasion Resistance - ISO 10545-6 | Compliant | Barefoot Ramp Test - DIN 51097 | A+B+C |
| Breaking Strength - ISO 10545-4 | Compliant | Chemical Resistance - ISO 10545-13 | Compliant |
| Coefficient of Thermal Linear Expansion - ISO 10545-8 | $\leq 7 \cdot 10^{-6} \cdot C^{-1}$ | Coefficient of Friction - B.C.R.A. Rep. CEC/81 | Asciutto > 0,40 / Bagnato > 0,40 |
| DCOF - B.C.R.A. Rep. CEC-81 | > 0.40 | Frost Resistance - ISO 10545-12 | Compliant |
| Coefficient of Restitution - ISO-10545-5 | Compliant | Moisture Expansion - ISO 10545-10 | $\leq 0,01 \%$ |
| Reaction to Fire - EN 13501-1 | A1fl | Regularity of Length & Width - ISO 10545-2 | Compliant |
| Resistance to Household Chemicals - ISO 10545-13 | A | Resistance To Staining - ISO 10545-14 | Class 5 |
| Resistance to Swimming Pool Salts - ISO 10545-13 | A | Booted Ramp Test - DIN 51130 | R10 |
| Slip Resistance (Ramp Test) - DIN 51130 | R10 | Thermal Shock Resistance - ISO 10545-9 | Compliant |
| Water Absorption - ISO 10545-3 | 0.2% | | |
| DCOF - ANSI A.137.1 | > 0.42 Wet | | |

LEED

MR

Recycled Content

20% pre-consumer
recycled material

akdo.com

COMMERCIAL · HOSPITALITY · RESIDENTIAL