


GAJA 18" X 36" SMOKE (TEXTURED) *Porcelain*



PART NUMBER	PROFILE	REPEAT
PO2413-1836T0	TILE	24
AVAILABILITY	GROUT JOINT	DIMENSIONS
IN STOCK	1/16"	17.72" x 35.43" = 4.36 sqft
THICKNESS	ORIGIN	
3/8"	Italy	

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	Compliant	Barefoot Ramp Test - DIN 51097	A+B+C
Breaking Strength - ISO 10545-4	Compliant	Chemical Resistance - ISO 10545-13	Compliant
Coefficient of Thermal Linear Expansion - ISO 10545-8	≤ 7 10-6•C-1	Coefficient of Friction - B.C.R.A. Rep. CEC/81	Asciutto > 0,40 / Bagnato > 0,40
DCOF - B.C.R.A. Rep. CEC-81	> 0.40	Frost Resistance - ISO 10545-12	Compliant
Coefficient of Restitution - ISO-10545-5	Compliant	Moisture Expansion - ISO 10545-10	≤ 0,01 %
Reaction to Fire - EN 13501-1	A1fl	Regularity of Length & Width - ISO 10545-2	Compliant
Resistance to Household Chemicals - ISO 10545-13	A	Resistance To Staining - ISO 10545-14	Class 5
Resistance to Swimming Pool Salts - ISO 10545-13	A	Booted Ramp Test - DIN 51130	R10
Slip Resistance (Ramp Test) - DIN 51130	R10	Thermal Shock Resistance - ISO 10545-9	Compliant
Water Absorption - ISO 10545-3	0.2%	TECHNICAL DATA	
FEATURES & STANDARD	SPECIFICATION		
DCOF - ANSI A.137.1	> 0.42 Wet		

LEED

MR

Recycled Content

20% pre-consumer
recycled material