AKDO

# RENAISSANCE 12" X 24" BELLA CANDIDO (P) *Porcelain*



PART NUMBER
PO2323-1224P0

PROFILE
TILE

AVAILABILITY
REGULAR STOCK

GROUT JOINT
1/16"

DIMENSIONS
11.81'' x 23.62'' = 1.937 sqft

THICKNESS
9mm

ORIGIN
Italy

NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

Renaissance is a popular choice for checkerboard layouts, however only certain colors within the collection can be paired together. please refer to the last page of the renaissance collection brochure for more information and consult your customer service representative to confirm caliber compatibility.

## APPLICATION AREA

| TRAFFIC | EXTERIOR | POOL | BACKSPLASH | FIREPLACE SURROUND | COUNTERTOP | INTERIOR |
|---|---|---|---|---|---|---|
| Residential | Wall Only Including Freeze/Thaw | Yes | Yes | Yes | No | Wall and Floor |

| SHOWER |
|---|
| Wall Only; Including Steam |

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

## TECHNICAL DATA

| FEATURES & STANDARD | SPECIFICATION | FEATURES & STANDARD | SPECIFICATION |
|---|---|---|---|
| Abrasion Resistance - ISO 10545-7 | Cl. 5 | Breaking Strength - ISO 10545-4 | Average Value 3200 N |
| Crazing Resistance - ISO 10545-11 | Resistant | Frost Resistance - ISO 10545-12 | Resistant |
| Bending Resistance - ISO 10545-4 | Average Value 50 N/mm2 | Regularity of Length & Width - ISO 10545-2 | ± 0,15% |
| Regularity of Rectangularity - ISO 10545-2 | ± 0,2% | Regularity of Straightness of Sides - ISO 10545-2 | ± 0,1% |
| Regularity of Thickness - ISO 10545-2 | ± 5% | Surface Quality - ISO 10545-2 | Compliant |
| Resistance To Staining - ISO 10545-14 | Cl. 4 | Resistance to Swimming Pool Salts - ISO 10545-13 | GA |
| Surface Flatness - ISO 10545-2 | ± 0,35% | Thermal Shock Resistance - ISO 10545-9 | Resistant |
| Water Absorption - ISO 10545-3 | Average Value 0,08% | | |