

RENAISSANCE 24" X 24" CHARMING (P) Porcelain



PART NUMBER

PROFILE TILE

AVAILABILITY IN STOCK

PO2315-2424P0

DIMENSIONS

 $23.64'' \times 23.64'' = 3.875 \text{ sqft}$

THICKNESS

TECHNIC

3/8"

1/16"

ORIGIN

GROUT JOINT

Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL FLOOR		TRAFFIC		EXTERIOR	STEAM SHOWER	WET AREA	POOL	
Yes	Resider Use Or	ntial Floor nly	Residential		Yes	Wall Only	Wall Only	Yes
BACKSF	PLASH	FIREPLACE SURROUND		INTERIOR				
Yes		Yes	Υ	/es				

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant
Coefficient of Thermal Linear Expansion - ISO 10545-8	² 7 10-6¥C-1	Frost Resistance - ISO 10545-12	Compliant
Coefficient of Restitution - ISO-10545-5	Compliant	Bending Resistance - ISO 10545-4	Compliant
Moisture Expansion - ISO 10545-10	² 0.01% (0.1mm/m)	Reaction to Fire - EN 13501-1	Alfl
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	А
Resistance to Swimming Pool Salts - ISO 10545-13	А	Booted Ramp Test - DIN 51130	RIO
Surface Flatness - ISO 10545-2	Compliant	Water Absorption - ISO 10545-3	0.2%

FEATURES & STANDARD

SPECIFICATION

DCOF - ANSI A. 137.1

> 0.42 Wet

LEED

MR	MR	MR
Recycled Content	Regional Materials	Sustainability Report
12 09/	2.0%	Available self-declared Cornerate Systemability Penert (CSD)

Declaration (EPD) conform to ISO14025

Material Ingredients

Available Health Product Declaration (HPD) in compliance with the Health Product Declaration Open Standard

Low Emitting Materials

Heat Island Effect

Energy Performance

akdo.com