

## RENAISSANCE 2" X 2" CHARMING (P) Porcelain



PART NUMBER PO2315-M002P0

GROUT JOINT 1/16"

ORIGIN Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

PROFILE

MOSAIC

DIMENSIONS

11.81" x 11.81" = .97 sqft

AVAILABILITY

IN STOCK

THICKNESS

**TECHNIC** 

3/8"

## APPLICATION AREA

WALL	FLOO	 R	TRAFFIC	EXTERIOR	STEAM	WET	POOL
					SHOWER	AREA	
Yes	Reside Use O	ntial Floor nly	Residential	Yes	Wall Only	Wall Only	Yes
BACKSF	PLASH	FIREPLACE SURROUND	INTERIOR				
Yes		Yes	Yes				

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

## TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant
Coefficient of Thermal Linear Expansion - ISO 10545-8	<sup>2</sup> 7 10-6¥C-1	Frost Resistance - ISO 10545-12	Compliant
Coefficient of Restitution - ISO-10545-5	Compliant	Bending Resistance - ISO 10545-4	Compliant
Moisture Expansion - ISO 10545-10	<sup>2</sup> 0.01% (0.1mm/m)	Reaction to Fire - EN 13501-1	Alfl
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	А
Resistance to Swimming Pool Salts - ISO 10545-13	А	Booted Ramp Test - DIN 51130	R1O
Surface Flatness - ISO 10545-2	Compliant	Water Absorption - ISO 10545-3	0.2%

FEATURES & STANDARD

**SPECIFICATION** 

DCOF - ANSI A. 137.1

> 0.42 Wet

## LEED

MR	MR	MR
Recycled Content	Regional Materials	Sustainability Report
13.8%	3.7%	Available solf-declared Corporate Sustainability Poport ICSPI

Declaration (EPD) conform to ISO14025

Material Ingredients

Available Health Product Declaration (HPD) in compliance with the Health Product Declaration Open Standard

Low Emitting Materials

Heat Island Effect

Energy Performance

akdo.com