

RENAISSANCE 24" X 24" MARQUINA (P) Porcelain



PART NUMBER

PROFILE TILE AVAILABILITY IN STOCK

GROUT JOINT

PO2317-2424P0

DIMENSIONS

THICKNESS

1/16"

23.64" x 23.64" = 3.875 sqft

3/8"

ORIGIN

Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR		TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL
Yes	Residen Use On	tial Floor ly	Residential	Yes	Wall Only	Wall Only	Yes
BACKSPI	LASH	FIREPLACE SURROUND	INTERIOR				
Yes		Yes	Yes				

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant
Coefficient of Thermal Linear Expansion - ISO 10545-8	² 7 10-6¥C-1	Frost Resistance - ISO 10545-12	Compliant
Coefficient of Restitution - ISO-10545-5	Compliant	Bending Resistance - ISO 10545-4	Compliant
Moisture Expansion - ISO 10545-10	² 0.01% (0.1mm/m)	Reaction to Fire - EN 13501-1	Alfl
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	А
Resistance to Swimming Pool Salts - ISO 10545-13	А	Booted Ramp Test - DIN 51130	R1O
Surface Flatness - ISO 10545-2	Compliant	Water Absorption - ISO 10545-3	0.2%

FEATURES & STANDARD

SPECIFICATION

DCOF - ANSI A. 137. 1

> 0.42 Wet

LEED

EQ112

Low-Emitting Materials

Zero V.O.C.

TECHNIC

Emissions

MR MR Recycled Content Regional Materials 13,7% 32%

conform to Global Reporting Initiative (GRI) Sustainability Report

Environmental Product Declaration

Available industry-wide Environmental Product Declaration (EPD) conform to ISO 14025

Material Ingredients

Available Health Product Declaration (HPD) in compliance with the Health Product Declaration Open Standard

Low Emitting Materials

No VOCs Emission

Energy Performance

Innovatione & Design