

RENAISSANCE 2" X 2" MARQUINA (P) Porcelain



PART NUMBER
PO2317-M002P0

MOSAIC DIMENSIONS

PROFILE

AVAILABILITY
REGULAR STOCK

 $11.81'' \times 11.81'' = .97 \text{ sqft}$

THICKNESS 3/8"

ORIGIN

1/16"

GROUT JOINT

Italy

NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

Renaissance is a popular choice for checkerboard layouts, however only certain colors within the collection can be paired together. please refer to the last page of the renaissance collection brochure for more information and consult your customer service representative to confirm coliber compatibility.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential	Wall Only Including Freeze/Thaw	Yes	Yes	Yes	No	Wall and Floor

SHOWER

Wall Only; Including Steam

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant
Coefficient of Thermal Linear Expansion - ISO 10545-8	² 7 10-6¥C-1	Frost Resistance - ISO 10545-12	Compliant
Coefficient of Restitution - ISO-10545-5	Compliant	Bending Resistance - ISO 10545-4	Compliant
Moisture Expansion - ISO 10545-10	² 0.01% (0.1mm/m)	Reaction to Fire - EN 13501-1	Alfl
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	А
Resistance to Swimming Pool Salts - ISO 10545-13	Α	Booted Ramp Test - DIN 51130	R1O
Surface Flatness - ISO 10545-2	Compliant	Water Absorption - ISO 10545-3	0.2%

DCOF - ANSI A. 137. 1

> 0.42 Wet

LEED

MR	MR	MR	MR
Recycled Content	Regional Materials	Sustainability Report	Environmental Product Declaration
13,7%	32%	Available self-declared Corporate Sustainability Report (CSR)	Available industry-wide Environmental Product

Material Ingredients

Available Health Product Declaration (HPD) in compliance with the Health Product Declaration Open Standard

Low Emitting Materials

Heat Island Effect

Energy Performance

akdo.com