## AKDO

### RENAISSANCE 12" X 24" MARQUINA (M) Porcelain



# PART NUMBERPROFILEAVAILABILITYPO2317-1224M1TILEREGULAR STOCKGROUT JOINTDIMENSIONSTHICKNESS1/16"11.81" x 23.62" = 1.94 sqft9mmORIGINLaboration of the state of the

#### NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot. Renaissance is a popular choice for checkerboard layouts, however only certain colors within the collection can be paired together. please refer to the

last page of the renaissance collection brochure for more information and consult your customer service representative to confirm caliber compatibility.

#### APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Standard Commercial	Wall Only Including Freeze/Thaw	Yes	Yes	Yes	No	Wall and Floor

#### SHOWER

Wall Only; Including Steam

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

#### TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION	
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant	
Coefficient of Thermal Linear Expansion - ISO 10545-8	<sup>2</sup> 7 10-6¥C-1	Frost Resistance - ISO 10545-12	Compliant	
Coefficient of Restitution - ISO-10545-5	Compliant	Bending Resistance - ISO 10545-4	Compliant	
Moisture Expansion - ISO 10545-10	<sup>2</sup> 0.01% (0.1mm/m)	Reaction to Fire - EN 13501-1	Alf	
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant	
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	A	
Resistance to Swimming Pool Salts - ISO 10545-13	A	Booted Ramp Test - DIN 51130	RIO	
Surface Flatness - ISO 10545-2	Compliant	Water Absorption - ISO 10545-3	0.2%	

DCOF - ANSI A.137.1

> 0.42 Wet

#### LEED

EQ112 Low-Emitting	g Materials	MR Recycled Content	MR Regional Materials	MR Sustainability Report
Zero Emissions	V.O.C.	13,7%	32%	Available self-declared Corporate Sustainability Report (CSR) conform to Global Reporting Initiative (GRI) Sustainability Report

Environmental Product Declaration

Available industry-wide Environmental Product Declaration (EPD) conform to ISO14025 Material Ingredients

Available Health Product Declaration (HPD) in compliance with the Health Product Declaration Open Standard

EQ

Low Emitting Materials

No VOCs Emission

SS

Heat Island Effect

Energy Performance

1,0 - 1,3 W/mK

ID

Innovatione & Design

Certificate Greenguard