

ARCADIA GRAIN BEECH (M) *Porcelain*



PART NUMBER
PO2384-GRAI00

PROFILE
TILE

REPEAT
48

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
3.86" x 18.31" = .491 sqft

THICKNESS
3/8"

ORIGIN
Spain

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

| WALL | FLOOR | TRAFFIC | EXTERIOR | STEAM SHOWER | WET AREA | POOL | BACKSPLASH | FIREPLACE SURROUND |
|------|-------|---------------------|----------|--------------|----------|------|------------|--------------------|
| Yes | Yes | Standard Commercial | Yes | Yes | Yes | Yes | Yes | Yes |

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

| FEATURES & STANDARD | SPECIFICATION | FEATURES & STANDARD | SPECIFICATION |
|------------------------------------|---------------------------|---|---------------------------|
| Abrasion Resistance - ISO 10545-7 | Moderate Commercial PEI 2 | Breaking Strength - ISO 10545-4 | > 1300 N |
| Chemical Resistance - ISO 10545-13 | GLA | Coefficient of Thermal Linear Expansion - ISO 10545-8 | < 9*10 ⁻⁶ ¼C-1 |
| Crazing Resistance - ISO 10545-11 | Resistant | Frost Resistance - ISO 10545-12 | Resistant |
| Heat Resistance - 96/603/CE | A1-A1FL | Bending Resistance - ISO 10545-4 | > 35N/mm ₂ |
| Water Absorption - ISO 10545-3 | > 0.5% | TECHNICAL DATA | |

| FEATURES & STANDARD | SPECIFICATION |
|---------------------|---------------|
| DCOF - ANSI A.137.1 | > 0.47 |