

MANSION 30" X 30" ARCADE (M) *Porcelain*



PART NUMBER
PO1830-303000

AVAILABILITY
IN STOCK

THICKNESS
3/8"

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

PROFILE
TILE

GROUT JOINT
1/16"

ORIGIN
Italy

REPEAT
8

DIMENSIONS
29.53" x 29.53" = 6.055 sqft

APPLICATION AREA

| WALL | FLOOR | TRAFFIC | EXTERIOR | STEAM SHOWER | WET AREA | POOL | BACKSPLASH | FIREPLACE SURROUND |
|-----------------|-------|------------------|----------|--------------|----------|------|------------|--------------------|
| Yes | Yes | Heavy Commercial | Yes | Yes | Yes | Yes | Yes | Yes |
| INTERIOR | | | | | | | | |
| Yes | | | | | | | | |

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

| FEATURES & STANDARD | SPECIFICATION | FEATURES & STANDARD | SPECIFICATION |
|--|---------------|---|-------------------|
| Abrasion Resistance - ISO 10545-6 | Compliant | Barefoot Ramp Test - DIN 51097 | A+B |
| Chemical Resistance - ISO 10545-13 | Compliant | Coefficient of Thermal Linear Expansion - ISO 10545-8 | ² 7 _ MK-1 |
| Frost Resistance - ISO 10545-12 | Compliant | Coefficient of Restitution - ISO-10545-5 | Compliant |
| Bending Resistance - ISO 10545-4 | Compliant | Moisture Expansion - ISO 10545-10 | ² 0.01% (0.1mm/m) |
| Reaction to Fire - EN 13501-1 | A1fl | Regularity of Length & Width - ISO 10545-2 | Compliant |
| Regularity of Rectangarity - ISO 10545-2 | Compliant | Regularity of Straightness of Sides - ISO 10545-2 | Compliant |
| Resistance to Household Chemicals - ISO 10545-13 | Compliant | Resistance to Swimming Pool Salts - ISO 10545-13 | Compliant |
| Booted Ramp Test - DIN 51130 | R10 | Surface Flatness - ISO 10545-2 | Compliant |
| Water Absorption - ISO 10545-3 | 0.2% | | |

TECHNICAL DATA

| FEATURES & STANDARD | SPECIFICATION |
|---------------------|---------------|
| DCOF - ANSI A.137.1 | Compliant |

LEED

EQ112

Low-Emitting Materials

< 1 mg/Kg

MR

Recycled Content

20% pre-consumer
recycled material