AKDO

MANSION 30'' X 30'' HALL (M) *Porcelain*



PART NUMBER
PO1832-303000

PROFILE
TILE

REPEAT
8

AVAILABILITY
REGULAR STOCK

GROUT JOINT
1/16"

DIMENSIONS
29.53'' x 29.53'' = 6.055 sqft

THICKNESS
9mm

ORIGIN
Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR
Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	Compliant	Barefoot Ramp Test - DIN 51097	A+B
Chemical Resistance - ISO 10545-13	Compliant	Coefficient of Thermal Linear Expansion - ISO 10545-8	[2] 7 _ MK-1
Frost Resistance - ISO 10545-12	Compliant	Coefficient of Restitution - ISO-10545-5	Compliant
Bending Resistance - ISO 10545-4	Compliant	Moisture Expansion - ISO 10545-10	[2] 0.01% (0.1mm/m)
Reaction to Fire - EN 13501-1	A1fl	Regularity of Length & Width - ISO 10545-2	Compliant
Regularity of Rectangularity - ISO 10545-2	Compliant	Regularity of Straightness of Sides - ISO 10545-2	Compliant
Resistance to Household Chemicals - ISO 10545-13	Compliant	Resistance to Swimming Pool Salts - ISO 10545-13	Compliant
Booted Ramp Test - DIN 51130	R10	Surface Flatness - ISO 10545-2	Compliant
Water Absorption - ISO 10545-3	0.2%		
DCOF - ANSI A.137.1	Compliant		

LEED

SS110	EQ112
Heat Island Reduction	Low-Emitting Materials
SRI >= 29	< 1 mg/Kg