

ARCHITETTO ANGOLO CALACATTA (H) W/ BRASS *Stone, Marble, Metal*



PART NUMBER
MB1203-ANGOH1

VARIATION
HIGH

THICKNESS
3/8"

NOTES

As a natural material, brass is prone to oxidation; a chemical reaction that occurs over time from exposure to air.

PROFILE
MOSAIC

GROUT JOINT
1/16"

AVAILABILITY
IN STOCK

DIMENSIONS
8" x 8" = .444 sqft

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER AREA	WET AREA	POOL	BACKSPLASH
Yes	Brass may scratch when used as floor covering.	Light Commercial	No	No	No	No	YES - Heat not to exceed 293° F
FIREPLACE SURROUND YES - Heat not to exceed 293° F							

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

Epoxy grout should be used when installing Architetto mosaics with metal.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
DCOF - ANSI A.137.1			