

ARCHITETTO MODULO CALACATTA (H) W/ BRASS *Stone, Marble, Metal*



PART NUMBER	PROFILE	AVAILABILITY
MB1203-MODUH0	MOSAIC	IN STOCK
GROUT JOINT	DIMENSIONS	THICKNESS
1/16"	12" x 12" = 1.0 sqft	3/8"
NOTES		
As a natural material, brass is prone to oxidation; a chemical reaction that occurs over time from exposure to air.		

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Brass may scratch when used as floor covering	Light Commercial	No	No	No	No	YES - Heat not to exceed 293° F
FIREPLACE SURROUND	INTERIOR						
YES - Heat not to exceed 293° F	Yes						

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

Epoxy grout should be used when installing Architetto mosaics with metal.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Dynamic Coefficient of Friction (DCOF) Testing
Test Name: ANSI A137.1
Results: >.42