

## 12" X 24" THASSOS STANDARD (H) Stone, Marble



PART NUMBER PROFILE AVAILABILITY
MB1232-1224H1 TILE REGULAR STOCK

GROUT JOINT DIMENSIONS THICKNESS 1/8" 12"  $\times 24$ " = 2 sqft (+/-) 3/8"

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

It is important to properly seal marble used in a shower/steam shower, and maintain the sealant regularly to ensure water beads off the tile.

## APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM	WET	POOL	BACKSPLASH	
				SHOWER	AREA			
Yes	Yes	Standard	No	YES - when properly	YES - when properly	No	Yes	
		Commercial		sealed	sealed			
FIREPLACE		INTERIOR						
SURRO	JND							
Yes		Yes						

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.