

12" PURE LINER THASSOS (P) *Stone, Marble*

| | | |
|---------------|-------------------------|--------------|
| PART NUMBER | PROFILE | AVAILABILITY |
| MB1232-PL12PO | TRIM | IN STOCK |
| GROUT JOINT | DIMENSIONS | THICKNESS |
| 1/16" | 11-9/16" x 1/2" = 1 lmf | 5/8" |



NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot. It is important to properly seal marble used in a shower/steam shower, and maintain the sealant regularly to ensure water beads off the tile.

APPLICATION AREA

| WALL | FLOOR | EXTERIOR FREEZE/THAW | STEAM SHOWER | WET AREA | POOL | BACKSPLASH | FIREPLACE SURROUND |
|------|-------|-------------------------|----------------------------|----------------------------|------|------------|-----------------------|
| Yes | No | No | YES - when properly sealed | YES - when properly sealed | No | Yes | Yes |

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

| FEATURES & STANDARD | SPECIFICATION | FEATURES & STANDARD | SPECIFICATION |
|---------------------|---------------|---------------------|---------------|
|---------------------|---------------|---------------------|---------------|

DCOF - ANSI A.137.1 _____